


Product: [1671J](#) 

50 Ohm Microwave, RG405, #24 SPC Coax, PVC Jacket



Product Description

RG-405/U type, 24 AWG solid .020" silver-plated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield (100% coverage), PVC jacket.

Technical Specifications

Product Overview

|                      |                |
|----------------------|----------------|
| Environmental Space: | Indoor/Outdoor |
|----------------------|----------------|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material                                   | Nominal Diameter | No. of Coax |
|-----|-----------|--|------------------|-------------|
| 24  | Solid     | SPCCS - Silver Plated Copper Covered Steel | 0.02 in          | 1           |

|                  |   |
|------------------|---|
| Conductor Count: | 1 |
|------------------|---|

Insulation

| Material                  | Material Trade Name | Nominal Diameter |
|---------------------------|---------------------|------------------|
| TFE - Tetrafluoroethylene | Teflon®             | 0.062 in         |

Outer Shield Material

| Type  | Layer | Material             | Coverage [%] |
|-------|-------|----------------------|--------------|
| Tape  | 1     | Copper Foil          | 100 %        |
| Braid | 2     | Tin-Filled Composite | 100 %        |

Outer Jacket Material

| Material                 | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | 0.127 in         |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR | Conductor Resistance | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|-----------------------|----------------------|--------------------------|---------------------|
| 64.2 Ohm/1000ft       | 64.2 Ohm/1000ft       |                      | 10.2 Ohm/1000ft          | 10.2 Ohm/1000ft     |

Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 29.5 pF/ft                           |

Inductance

| Nominal Inductance |
|--------------------|
| 0.07 µH/ft         |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 50 Ohm                           |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 500 MHz         | 15 dB/100ft         |
| 1000 MHz        | 22.2 dB/100ft       |
| 2000 MHz        | 32.8 dB/100ft       |
| 3000 MHz        | 41.2 dB/100ft       |
| 5000 MHz        | 54.9 dB/100ft       |
| 7000 MHz        | 66.4 dB/100ft       |
| 10000 MHz       | 81.2 dB/100ft       |
| 15000 MHz       | 102 dB/100ft        |
| 18000 MHz       | 113 dB/100ft        |
| 20000 MHz       | 120 dB/100ft        |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.46 ns/ft    | 69.5 %                                   |

Power Rating

| Frequency [MHz] | Max. Power Rating [W] |
|-----------------|-----------------------|
| 500 MHz         | 180 W                 |
| 1,000 MHz       | 119 W                 |
| 2,000 MHz       | 79 W                  |
| 3,000 MHz       | 62 W                  |
| 5,000 MHz       | 46 W                  |
| 7,000 MHz       | 37 W                  |
| 10,000 MHz      | 30 W                  |
| 15,000 MHz      | 24 W                  |
| 18,000 MHz      | 21 W                  |
| 20,000 MHz      | 20 W                  |

Voltage

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 1500 V RMS            | 30 V RMS          |

VSWR

| Frequency [MHz] | Max. VSWR |
|-----------------|-----------|
| 500 MHz         | 1.1:1     |
| 20000 MHz       | 1.3:1     |

Temperature Range

|                       |                 |
|-----------------------|-----------------|
| Non-UL Temp Rating:   | 105°C           |
| UL Temp Rating:       | 105°C           |
| Operating Temp Range: | -40°C To +105°C |

Mechanical Characteristics

|                                      |               |
|--------------------------------------|---------------|
| Bulk Cable Weight:                   | 16 lbs/1000ft |
| Max Recommended Pulling Tension:     | 26 lbs        |
| Min Bend Radius (Overall):           | 1 in          |
| Min Bend Radius During Installation: | 0.125 in      |
| Min Flexing Radius:                  | 0.375 in      |

Standards

|               |                             |
|---------------|-----------------------------|
| UL AWM Style: | UL Style 10245 (30 V 105°C) |
| RG Type:      | 405/U Type                  |

Applicable Environmental and Other Programs

|                                    |     |
|------------------------------------|-----|
| EU Directive 2000/53/EC (ELV):     | Yes |
| EU Directive 2003/11/EC (BFR):     | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE):    | Yes |

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | No                            |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01                    |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |

Suitability

|                        |     |
|------------------------|-----|
| Suitability - Indoor:  | Yes |
| Suitability - Outdoor: | Yes |

Flammability, LS0H, Toxicity Testing

|                     |                 |
|---------------------|-----------------|
| Other Flammability: | Horizontal Wire |
| UL voltage rating:  | 30 V RMS        |

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #        | Color  | UPC          | Length   | Footnote |
|---------------|--|--------------|----------|----------|
| 1671J 010100  | Black  | 612825120315 | 100 ft   |          |
| 1671J 0101000 | Black  | 612825120322 | 1,000 ft | V        |
| 1671J 010500  | Black  | 612825120339 | 500 ft   | V        |
| Footnote:     | V - 250' PUT-UP EXACT LENGTH MAXIMUM OF 3 PIECES, MINIMUM LENGTH 50'. 500' PUT-UP EXACT LENGTH MAXIMUM OF 5 PIECES, MINIMUM LENGTH 50'. 1000' PUT-UP EXACT LENGTH MAXIMUM OF 8 PIECES, MINIMUM LENGTH 50'. |              |          |          |

Product Notes

|        |   |
|--------|---|
| Notes: | Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---|

History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.290 Revision Date: 08-22-2019 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.