

NX-3200/3300

VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models with 14-pin Universal connector are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.



Full Keypad Model
Standard & Basic Models



7-color Light Bar Indicator

14-pin Universal Connector offers reliable connectivity even in harsh environment with a wide-range of accessories.

FEATURES

- Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols
- NXDN Conventional and Type-C & Gen2 Trunking
- DMR Tier II & Site Roaming
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 5-Line Text Message Frame (3 Lines of Text, icon & key guide)
- 7-color Light Bar Indicator on the top panel
- 4-way Directional-pad (D-pad) for intuitive control and operation
- Built-in GPS Receiver/Antenna for effective fleet management
- Built-in Bluetooth for hands-free operation – Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
- Optional DES and AES Encryption
- Built-in Motion Sensor (Man-down, Stationary and Motion Detection)
- IP54/55/67 and MIL-STD-810 C/D/E/F/G
- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 512 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option

- Intrinsically Safe Option (Available later)
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- Optional ARC4 Encryption
- Energy Efficient

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Multi-Protocol

Unsurpassed interoperability for Public Safety and Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

<ul style="list-style-type: none"> ■ KNB-55L/57L/78L Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh) ■ KNB-56N Ni-MH Battery Pack (7.2 V/1400 mAh) ■ KNB-79LC* Li-ion Battery Pack (7.4 V/2860 mAh, Intrinsically Safe) ■ KBP-5 Battery Case (6 AA) ■ KSC-25LSK/25S Rapid Charger (Li-ion Only/Tri-Chem) 	<ul style="list-style-type: none"> ■ KSC-256K Multiple Charger (6-pocket) ■ KMB-30 Mounting Bracket (for KSC-256) ■ KVC-23 Vehicular Charger ■ KRA-22 VHF Low Profile Helical Antenna ■ KRA-23 UHF Low Profile Helical Antenna 	<ul style="list-style-type: none"> ■ KRA-25 High Gain Whip Antenna ■ KRA-26 VHF Helical Antenna ■ KRA-27 UHF Whip Antenna ■ KRA-28 Broadband VHF Whip Antenna ■ KRA-41 VHF/UHF Stubby Antenna 	<ul style="list-style-type: none"> ■ KRA-42 VHF/UHF Stubby Antenna ■ KEP-1 Earphone (3.5mm) ■ KMC-41D Speaker Microphone (IP54/55) ■ KMC-54WD Speaker Microphone (with dual-sided 2-mic for superior ANR, IP67) 	<ul style="list-style-type: none"> ■ KBH-11 Belt Clip (2.5") ■ KPG-180P OTAP Manager ■ KLH-206 Leather Case ■ KLH-207 Nylon Case
---	--	---	---	--

* Available Later

All accessories may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories.

Specifications

	NX-3200	NX-3300		NX-3200	NX-3300
GENERAL			RECEIVER		
Frequency Range	136-174 MHz	400-520 MHz	Sensitivity	NXDN® 6.25 kHz Digital (3% BER) 0.20 µV NXDN® 12.5 kHz Digital (3% BER) 0.25 µV DMR 12.5 KHz Digital (5% BER) 0.30 µV DMR 12.5 KHz Digital (1% BER) 0.45 µV Analog (12dB SINAD) 0.25 µV	
Max. Channels Per Radio	Up to 1000 CH with option		Selectivity	Analog @ 12.5 kHz 65 dB Analog @ 25 kHz 72 dB	
Number of Channels	512 (64 for no LCD models)		Intermodulation	70 dB	
Number of Zones	128 (4 for no LCD models)		Spurious Rejection	70 dB	
Channel Spacing	Analog 12.5/15/25*/30* kHz Digital 6.25 kHz/12.5 kHz		Audio Distortion	3%	
Power Supply	7.5V DC ± 20%		Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)	
Battery Life 5-5-90	(FDMA / TDMA)		TRANSMITTER		
KNB-55L (1,480 mAh)	Approx. 8 hours / Approx. 9.5 hours		RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W	
KNB-56N (1,400 mAh)	Approx. 8 hours / Approx. 9 hours		Spurious Emission	70 dB	
KNB-57L (2,000 mAh)	Approx. 11 hours / Approx. 13.5 hours		FM Hum & Noise	Analog @ 12.5 kHz 40 dB Analog @ 25kHz 45 dB	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)		Audio Distortion	Less than 3%	
Frequency Stability	±2.0 ppm		Digital Protocol	ETSI TS 102 361-1, -2, -3	
Dimensions	(W x H x D) Projections Not Included		Emission Designator	16K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	
Radio Only	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)				
KNB-55L (1,480 mAh)	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)				
KNB-56N (1,400 mAh)	2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)				
KNB-57L (2,000 mAh)	2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)				
Weight Radio Only	7.8 oz (220 g)				
KNB-55L (1,480 mAh)	11.1 oz (315 g)				
KNB-56N (1,400 mAh)	14.5 oz (410 g)				
KNB-57L (2,000 mAh)	12.0 oz (340 g)				
FCC ID	K44479000	K44479100			
IC Certification	282F-479000	282F-479100			

*1.25 and 3.0 kHz are not included in the models sold in the USA or US territories. Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology.

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® & FleetSync® are a registered trademarks of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration Shock	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection*	IP54/55/67				

*Radio must equip accessory cover.



JVCKENWOOD USA Corporation
 Communications Sector Headquarters
 3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265
 Order Administration/Distribution
 P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
 Canadian Headquarters and Distribution
 6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
 JVCKENWOOD Corporation
 ASD#53717 Printed in USA