

KENWOOD



TK-5720/5820

VHF/UHF FM & P25 Digital Mobile Radio



FleetSync®

GENERAL FEATURES

- 50W (136-174 MHz)
- 45W (400-470, 450-520, 380-400*MHz)
- 128 Zones / 512 Channels
- Enhanced Kenwood Audio
- Emergency Features
- Public Address (KAP-2 Required)
- Time Out Timer
- Busy Channel Lockout
- Ignition Sense
- Timed Power Off
- DB-25 & 9-Pin Accessory Connectors
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- Transceiver Password
- Date & 12/24 Hour Time Clock
- KPG-112D/DN Windows® FPU
- Flash Firmware Upgrading
- Easy Option Ports (26-pin)
- Voice Guide & Storage (option)
- MIL-STD-810 C/D/E/F/G
- MIL-STD-810 C/D/E/F/G
- MIL-STD Mic (included)
- MIL-STD 12-Key DTMF Mic Option

FRONT PANELS/CONTROL HEADS

- Dash & Remote Mount
- Dual Control Head Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator

FRONT PANELS/CONTROL HEADS Cont.

- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio

P25 DIGITAL

- P25 Digital Conventional
- AMBE+2™ Enhanced VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor / Check, Radio Inhibit
- Encryption Key Zeroize and Retention
- DES Encryption Module
- AES & DES Encryption Module
- P25 Digital Trunking Option

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan
- Scan Lists¹
- Conventional Scan
- Dual Priority Scan

FM

- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode / Encode
- DTMF Encode / Decode / Stun
- Special Alert Tone Patterns
- Companded Audio

FleetSync® / II (FM)

- PTT ID Digital ANI
- Caller ID Display
- Status Messaging
- Emergency & Stun Statuses
- Selective & Group Call
- Text Messaging
- Send/Display GPS

MDC-1200

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit

*For U.S. federal government & export sales



Options

■ **KMC-35**
Microphone



■ **KMC-36**
Microphone with Keypad



■ **KMC-9C**
Control Station Desktop Microphone



■ **KES-5**
External Speaker



■ **VGS-1**
Voice Guide & Storage Unit




■ **KRK-10**
Panel Remote Kit



■ **KRK-13**
Dual Control Head Remote Kit



■ **KPS-15**
DC Power Supply



■ **KAP-2**
Horn Alert/PA Relay Unit



■ **KCT-23M**
DC Cable (10 feet)



■ **KCT-23M3**
DC Cable (23 feet)

KCT-23M3

■ **KCT-46**
Ignition Sense Cable



■ **KLF-2**
Line Noise Filter



■ **KMB-10**
Lock Key Adapter



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-5720	TK-5820
GENERAL		
Frequency Range		
Type 1	136-174 MHz	450-520 MHz
Type 2		400-470 MHz
Type 3	-	380-400 MHz
Number of Channels		512
Zones		128
Max. Channels per Zone		250
Channel Spacing		
Analog	12.5 / 15 / 25 / 30 kHz	12.5 / 25 KHz
Digital	12.5 kHz	12.5 kHz
Operating Voltage		13.6 V DC ± 20 %
Operating Temperature Range	-22° F to +140° F (-30° C to +60° C)	
Frequency Stability	± 2.0 ppm	± 1.0 ppm
Antenna Impedance		50 Ω
Dimensions (W x H x D) (projections not included)	6.30 x 1.77 x 6.18 in. (160 x 45 x 157 mm.)	
Weight (net)	3.04 lbs (1.38 kg)	
FCC ID		
Type 1	K44378602	K44378704
Type 2		K44378705
Type 3	-	-
IC Certification		
Type 1	282F-378602	282F-378704
Type 2		282F-378705
Type 3	-	-

FleetSyn® is a registered trademark of JVCKENWOOD Corporation.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
The P25 Logo is used under license and is a registered trademark of the Project 25 Technology Interest Group.

Specifications are subject to change without notice, due to advancements in technology.

Model	TK-5720	TK-5820
RECEIVER		
Sensitivity		
Digital (5 % BER)		0.25 µV
Digital (1 % BER)		0.40 µV
Analog 12 dB SINAD		0.25 µV
Selectivity		
Digital		-60 dB
Analog @ 25kHz		-80 dB
Analog @ 12.5 kHz		-70 dB
Intermodulation Distortion		
Digital		-73 dB
Analog		-75 dB
Spurious & Image	-90 dB	-85 dB
Audio Distortion	Less than 3.0 %	
Audio Output	4 W / 4 Ω	
TRANSMITTER		
RF Power Output	50 W to 10 W	45 W to 10 W*
Spurious & Harmonics	73 dB	75 dB
FM Hum & Noise		
Analog @ 25 kHz		50 dB
Analog @ 12.5 kHz		45 dB
Audio Distortion	Less than 3 %	
Modulation	11K0F3E, 16K0F3E, 8K10F1E, 8K10F1D	

Analog measurements made per TIA/EIA 603
Digital measurements made per TIA/EIA 102CAAA

* Type 1: 45W to 10W for 450-490MHz.
40W to 10W for 490-512MHz.
35W to 10W for 512-520MHz.
Type 2: 45W to 10W for 400-470MHz.

footnotes from front:
¹ Analog mode only.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54: Radio Itself				
	IP54/55: Remote Head				

KENWOOD

JVCKENWOOD USA Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
JVCKENWOOD Corporation

A528817 Printed in USA