

KENWOOD

Listen to the Future



TK-5910

700/800MHz FM & P25 Digital Mobile Radio



GENERAL FEATURES

- 30W (763-806 MHz)
- 35W (806-870 MHz)
- 100 Zones / 1024 Channels
- Personality Lists
- Zone/CH Voice Announce
- Emergency Features
- Tactical Group
- Intercom¹
- Public Address
- Time Out Timer
- Busy Channel Lockout
- Ignition Sense²
- Timed Power Off
- DB-25 & 9-Pin Accessory Connectors³
- Transceiver Password
- Date & 12/24 Hour Time Clock
- Windows[®] Programming & Tuning⁴
- Windows[®] Firmware Uploading⁴
- Field-Programming & Tuning
- Voice Guide & Storage (option)*
- MIL-STD 810 C/D/E/F, IP-54
- MIL-STD Noise-Cancel Mic (included)
- MIL-STD 12-Key DTMF Mic Option

MOUNTING CONFIGURATIONS

- Dash Mount
- Single Control Head Remote Mount
- Handheld Control Remote Mount
- Dual Control Head Remote Mount

FRONT PANELS/CONTROL HEADS

- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Transmit LED
- Busy/Call Alert/Warn LED
- LCD Brightness Control
- Backlit Keys
- MIL-STD 810 512.X Driven Rain

KCH-14 Front Panel

- 12-Character Alphanumeric Aliases
- 5 PF & UP/DOWN Keys
- PF Key Label Inserts
- Built-in Front Speaker

KCH-15 Front Panel

- 14-Character Alphanumeric Aliases
- 11 PF Keys & UP/DOWN Keys
- PF Key Label Inserts
- External Speaker Required

KHC-16 Handheld Control Head

- 14-Character Alphanumeric Aliases
- 5 PF Keys & UP/DOWN/LEFT/RIGHT Keys
- Front PF Keys Name Display
- 12-Key DTMF/Function Keypad
- External Speaker Required

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan
- Scan Lists
- Conventional Scan
- Limited Talk Group Scan*
- Priority Monitor Scan
- Dual Priority Scan

FM

- QT / DQT
- Operator Selectable Tone⁵
- DTMF Encode⁶
- Horn Alert Output
- Companded Audio
- NPSPAC Channels

P25 DIGITAL

- P25 Digital Conventional
- P25 Digital Trunking
- AMBE+2™ Enhanced VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- RSSI Indicator
- Remote Monitor / Check, Radio Inhibit
- Encryption Key Zeroize & Retention
- DES Encryption Module
- AES & DES Encryption Module
- KPG-43AM Radio Program/Soft-Key Loader Cable
- KPG-94 KVL Device Key Loader Cable⁷
- P25 GPS Location*
- P25 OTAR Option*


*Future availability



Options

KCH-14

Basic Remote Control Head



KCT-18

Ignition Sense Cable



VGS-1

Voice Guide & Storage Unit



KMC-27

Microphone (MIL-SPEC noise-canceling)



KCH-15

Full-Featured Remote Control Head



KCT-22

Remote Control Cable



KES-5

External Speaker (20W)



KCH-16

Hanheld Control Head



KRK-5

Single Control Head Remote Kit



KCT-23

DC Power Cable



KMC-9B

Desktop Microphone




KRK-11

Hanheld Control Head Interface Kit




KRK-6DH

Dual Control Head Remote Kit



KPG-94

KVL Device Key Loader Cable



KMC-28

Keypad Microphone (MIL-SPEC noise-canceling)



All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-5910
GENERAL	
Frequency Range	
Receive	763-776, 851-870 MHz
Transmit	763-776, 793-806, 806-825, 851-870 MHz
Number of Channels	1024
Zones	100
Max. Channels per Zone	512
Channel Spacing	
Analog	12.5 / 25 KHz
Digital	12.5 kHz
PLL Channel Steps	12.5 kHz
Operating Voltage	13.6V DC $\pm$ 15 %
Current Drain	
Standby	Less than 0.45A
Receive	Less than 2.3A
Transmit	Less than 13A
Duty Cycle	Transmit: 20%
Operating Temperature Range	-22° F to +140° F (-30° C to +60° C)
Frequency Stability	$\pm$ 1.5 ppm (-22° F to +140° F)
Antenna Impedance	50 Ω
Dimensions (W x H x D) (projections not included)	
RF Deck only	7.01 x 2.36 x 10.3 in. (178 x 60 x 261 mm.)
with KCH-14 or 15	7.05 x 2.36 x 11.7 in. (179 x 60 x 296 mm.)
Weight	
RF Deck only	6.6 lbs. (3.0 kg)
with KCH-14	7.3 lbs. (3.3 kg)
with KCH-15	7.3 lbs. (3.3 kg)
FCC ID	K44421000
IC Certification	282F-421000

Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
The P25 Logo is used under license and is a registered trademark of the Project 25 Technology Interest Group.

Kenwood follows a policy of continuous advancement in development.
For this reason specifications may be changed without notice.

Model	TK-5910
RECEIVER	
Sensitivity	
Digital (5 % BER)	0.25 μ V
Digital (1 % BER)	0.40 μ V
Analog 12 dB SINAD	0.25 μ V
Selectivity	
Digital	-63 dB
Analog @ 25 kHz	-80 dB
Analog @ 12.5 kHz	-70 dB
Intermodulation Distortion	-80 dB
Spurious & Image	-85 dB
Audio Distortion	
Digital	Less than 1.0 %
Analog	Less than 2.0 %
Audio Output	
Internal (KCH-14)	@ 3% 1.5 W / 8 Ω / @ 5% 1.625 W / 8 Ω
External	@ 3% 12 W / 4 Ω / @ 5% 13 W / 4 Ω
TRANSMITTER	
RF Power Output	
763-776, 793-806 MHz	30 W to 2 W
806-825, 851-870 MHz	35 W to 2 W
Spurious & Harmonics	-80 dB
FM Hum & Noise	
Analog @ 25 kHz	45 dB
Analog @ 12.5 kHz	40 dB
Microphone Impedance	600 Ω
Audio Distortion	Less than 2 %
Modulation Limiting	
Analog @ 25 KHz	$\pm$ 5 kHz
Analog @ NPSPAC	$\pm$ 4 kHz
Analog @ 12.5 KHz	$\pm$ 2.5 kHz
Modulation	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 14K0F3E

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Digital measurements made per TIA/EIA 102CAAA and specifications shown are typical.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure II	507.2/Procedure II	507.3/Procedure II	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I, II	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I, II	514.4/Procedure I, II	514.5/Procedure I, II
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V, VI	516.4/Procedure I, IV, V, VI	516.5/Procedure I, IV, V, VI
International Protection Standard				
Dust & Water Protection	IP54: Radio Itself			

footnotes from front:

¹ Intercom: Dual Head capable remote mounts only.

² KCT-18 ignition sense cable option required.

³ DB-25 ACC: I/O's for dispatch consoles, desktop remotes, vehicle intercom/PA units, motorcycle PTT/headset kits, PC Laptop /Data Modems, GPS/AVL Modems; DB-25 (9 Prog. AUX I/O's & 2 Prog. AUX Outputs); 1 Prog Input (on Control Head).

⁴ KPG-95D Software: Windows® 98 /INT 12000 /Me /XP /VISTA (32 bit) compatible.

⁵ Operator Selectable Tone (40 QT.DQT code pairs).

⁶ DTMF Manual Encode (KMC-28/KCH-16), Auto-Dial (9 numbers).

⁷ KPG-94 adapts the Motorola, KVL3000/3000 Plus Key Loader to the TK-5910.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8


www.kenwoodusa.com



ADS#39909 Printed in USA