

KENWOOD



TK-5720/5820

VHF/UHF FM & P25 Digital Mobile Radio



FleetSync®

GENERAL FEATURES

- 50W (136-174 MHz)
- 45W (400-470, 450-520, 380-400*MHz)
- 128 Zones / 512 Channels
- Enhanced Kenwood Audio
- Emergency Features
- Public Address (KAP-2 Required)
- Time Out Timer
- Busy Channel Lockout
- Ignition Sense
- Timed Power Off
- DB-25 & 9-Pin Accessory Connectors
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- Transceiver Password
- Date & 12/24 Hour Time Clock
- KPG-112D/DN Windows® FPU
- Flash Firmware Upgrading
- Easy Option Ports (26-pin)
- Voice Guide & Storage (option)
- MIL-STD-810 C/D/E/F/G
- MIL-STD-810 C/D/E/F/G
- MIL-STD Mic (included)
- MIL-STD 12-Key DTMF Mic Option

FRONT PANELS/CONTROL HEADS

- Dash & Remote Mount
- Dual Control Head Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator

FRONT PANELS/CONTROL HEADS Cont.

- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio

P25 DIGITAL

- P25 Digital Conventional
- AMBE+2™ Enhanced VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor / Check, Radio Inhibit
- Encryption Key Zeroize and Retention
- DES Encryption Module
- AES & DES Encryption Module
- P25 Digital Trunking Option

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan
- Scan Lists¹
- Conventional Scan
- Dual Priority Scan

FM

- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode / Encode
- DTMF Encode / Decode / Stun
- Special Alert Tone Patterns
- Companded Audio

FleetSync® / II (FM)

- PTT ID Digital ANI
- Caller ID Display
- Status Messaging
- Emergency & Stun Statuses
- Selective & Group Call
- Text Messaging
- Send/Display GPS

MDC-1200

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit

**For U.S. federal government & export sales*

