

NX-240V/340U

NEXEDGE® VHF/UHF DIGITAL & FM PORTABLE RADIOS

NXDN® **FleetSync®**

Your business will have to adopt digital radios sooner or later, you know that, but you probably wonder when to make the extra investment. A leap into the unknown? Not with the new NEXEDGE® NX-240V/340U. It operates in both analog FM and NXDN® digital modes, offering a cost-effective way to migrate smoothly from legacy systems while discovering the benefits of advanced digital technology – including increased effective coverage area, low noise for superior clarity, and inherent secured voice. All this comes in a tough, compact radio that is easy to operate, delivers high-powered audio, and ensures round-the-clock reliability. Don't delay the opportunity to expand the potential of your business.

Features

GENERAL Multiple Scan

- 4-Color LED (Blue / Red / Green / Orange)
- 2 PF Keys
- 16-Position Mechanical Selector
- Zone/Channel Number Voice Announcement, VOX Ready
- Emergency Call, Remote Stun/Kill
- Lone Worker Alert (per channel)
- Time Out Timer, Busy Channel Lockout
- Low Battery Warning, Battery Saver
- KPG-170D Windows® FPU
- Wireless Cloning, Password Protection
- PTT Release Tone, Minimum Volume, Mic Sense
- MIL-STD-810 C/D/E/F/G
- IP54/55 Water & Dust Intrusion
- Intrinsically Safe Option

DIGITAL Over-The-Air Alias (TX only)

- Paging Call, Individual Call & Conference Group Call
- Status Messaging, Remote Monitor
- Site Roaming, Late Entry
- NXDN ESN

ANALOG FleetSync® II, MDC-1200, DTMF

- QT/DQT/2-tone, Compander, Squelch Level

NXDN Digital Air Interface

NEXEDGE radios employ NXDN®, an FDMA digital air interface with AMBE+2™ voice coding technology, unique filtering and a 4-level FSK modulation technique with low bit error rate (BER) even at weak RF signal strengths.

Enhanced Audio Quality

AMBE+2™ voice coding technology, accurately replicates natural human speech nuances for superior voice quality, even at highway speeds. Additionally, the powerful 36mm-diameter speaker delivers up to 1 watt audio output, providing undeniably clearer and crisper audio.



Ultimate Performance & Ergonomic Design

RF output power is 5W for both VHF (NX-240V) and UHF (NX-340U) models. Additionally, the UHF frequency coverage on the NX-340U is 70 MHz (excludes Type 3). Slim contours and ergonomic design of the NX-240V/340U make it comfortable to hold, while dimples on both sides ensure a firm grip.

Analog and Digital Modes

The NX-240V/340U is effectively two radios in one – analog and digital – operating on 12.5/25* kHz in analog zones, and on 6.25/12.5 kHz NXDN® in digital zones. For convenience, a PF key can be used to switch between zones.

NXDN Conventional

Compatible with NEXEDGE® Digital Conventional Mode, this radio offers 64 RAN (Radio Access Numbers) and individual & conference group calling to ensure expeditious communications.

NXDN Type-D Trunking*

The NX-240V/340U supports the NXDN® Type-D digital trunking protocol.* With this architecture, also known as distributed or decentralized trunking, all channels can operate as traffic channels without the need for a dedicated control channel. This makes it possible to develop an efficient and reliable yet affordable trunking system. Type-D trunking is thus suitable for users considering migration to a small scale, single site digital trunking system.

Accessories Included

- KNB-45L Li-ion Battery Pack • KSC-35S Rapid Charger • KRA-26 VHF Helical Antenna (Std. Length) with NX-240V • KRA-27 UHF WHIP ANTENNA (Std. Length) with NX-340U • KBH-10 Belt Clip

Accessories

All accessories may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories.

KNB-29N
Ni-MH Battery Pack
(1,500mAh)



KNB-45L
2,000mAh/7.4V
Li-Ion Battery Pack



KNB-69L
2,550mAh/7.4V
Li-Ion Battery Pack



KNB-82LCM
2,000mAh/7.4V, Intrinsically
Safe Li-Ion Battery Pack



KSC-43K
Dual Chemistry
Fast Charger
For the KNB 29N/45L/69L/82LCM



KVC-22
DC Vehicular
Charger Adapter



KRA-22/23
VHF/UHF Low Profile
Helical Antenna



KRA-26/ 27
VHF Helical Antenna
UHF Whip Antenna



KRA-41/42
VHF/UHF Stubby Antenna



KMC-45D
Speaker Microphone



KMC-21
Compact Speaker
Microphone



KEP-2
Earphone Kit for
KMC-45D (2.5mm plug)



KHS-7
Single Muff Headset



KHS-7A
Single Muff Headset
with In-line PTT



KHS-8BL
2-Wire Palm Mic
with Earphone (Black)



KHS-9BL
3-Wire Lapel Mic
with Earphone (Black)



KHS-22A
Behind-the-head
Headset with PTT



KHS-26
Earbud In-line
PTT Headset



KHS-27A
D-Ring In-line
PTT Headset



KHS-31C
C-Ring PTT Ear
Hanger Headset



KMB-28AK
Six Unit Charger
Adapter (for six
KSC-35SK chargers)



KBH-10
Belt Clip



KLH-187
Nylon Case



Specifications

General	NX-240V	NX-340U
Frequency Range Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Number of Channels	32	
Number of Zones	2	
Max. Channels per Zone	16	
Channel Spacing Analog Digital	30*/25*/15/12.5 kHz 12.5 kHz/6.25 kHz	25*/12.5 kHz
Power Supply	7.5V DC ± 20%	
Battery Life KNB-45L (2000mAh)	(5-5-90 during hi-power battery saver: OFF/ON) 10 / 12 hours	
Operating Temperature	-22° F ~ +140° F (-30° C ~ +60° C)	
Frequency Stability	± 2.0 ppm	± 1.0 ppm
Antenna Impedance	50 Ω	
Dimensions Radio with KNB-45L	(W x H x D) Projections Not Included 213 x 48 x 139 in (54 x 122 x 35.3 mm)	
Weight Radio Only Radio with KNB-45L	5.8 oz (165 g) 9.9 oz (281 g)	
FCC ID Type 1 Type 2	ALH443700	ALH443800 ALH443801

*Ver. 2.0 models are compatible with Analog 25 kHz and 30 kHz as well as Digital 12.5 kHz Channel Spacing. However, Analog 25 kHz and 30 kHz are not included in the models sold in the USA or US territories.
Analog measurements made per TIA603. Specifications are measured according to applicable standards.
Specifications are subject change without notice, due to advancements in technology.

Receiver	NX-240V	NX-340U
Sensitivity NXDN® 6.25 kHz Digital (3% BER) NXDN® 12.5 kHz Digital (3% BER) Analog (12dB SINAD)	0.25 µV 0.25 µV 0.25 µV	
Selectivity Analog @ 12.5kHz Analog @ 25kHz	60 dB 70 dB	
Intermodulation Distortion	70 dB	
Spurious Response	70 dB	
Audio Distortion	Less than 10%	
Audio Output Power	1 W / 12 Ω (Internal Output) 500mW / 8 Ω (External Output)	

Transmitter	NX-240V	NX-340U
RF Power Output (High / Low)	5 W / 1 W	
Spurious Response	70 dB	
FM Hum & Noise Analog @ 12.5kHz Analog @ 25kHz	40 dB 45 dB	
Audio Distortion	Less than 10%	
Emission Designator	16K0F3E, 1K0F3E, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D, 8K30F1E, 8K30F1D, 8K30F7W	

FleetSync® is a registered trademark of JVC KENWOOD Corporation.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
NXDN® is a trademark of JVC KENWOOD Corporation and Icom Inc.
NEXEDGE® is a registered trademark of JVC KENWOOD Corporation.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	5001/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	5011/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection*	IP54/55*				

* To meet MIL-810 and IP grade, the 2-pin connector must be secure.

JVC KENWOOD USA Corporation
Communications Sector Headquarters
1440 Corporate Drive | Irving, TX 75038

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

KENWOOD Communications
Global Website



comms.kenwood.com



ISO9001 Registered
Communications Systems Business Unit
JVC KENWOOD Corporation

ADS#19119 Print in U.S.A.