

KENWOOD



TK-2170/3170

Compact VHF/UHF FM Portable Radios

FleetSync®

GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 4 W (450-490, 400-430 MHz) Models
- Conventional Zones
- 128 Channels / 128 Zones¹
- Single Priority Scan
- Single & Multi-Zone Scan
- List Scan
- 8 Character Alphanumeric Aliases
- Backlit LCD
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- 4 Front Panel PF keys
- 3 Side PF Keys
- Orange Emergency / AUX Key
- 12-Key DTMF / PF Keypad Models²
- 500 mW Audio Power
- Enhanced Kenwood Audio
- Companded Audio
- VOX Ready
- Voice Inversion Scrambler Built-in
- Encryption / ANI Board Control
- Easy Option Port (20-Pin)
- Emergency Call Features
- Emergency Man-Down Option
- QT / DQT
- Two-Tone Decode³
- Single / Two-Tone Encode³

- Operator Selectable Tone³
- DTMF Encode / Decode⁴
- Special Alert Tone Pattern⁵
- Call Key⁶
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- Speaker Mic Options
- Windows® Programming & Tuning⁷
- Windows® Firmware Uploading⁷
- Field Programming & Tuning
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Intrinsically Safe Option

FleetSync®

- PTT ID Digital ANI
- Selective Call & Group Call⁸
- Status Messaging⁸
- Emergency Status
- Caller ID Display⁸
- Short Text Messages⁸
- PC Serial Interface



Keypad model also available.

Options

- **KNB-55L**
Li-ion Battery Pack
(1,480mAh)
- **KNB-56N**
Ni-MH Battery Pack
(1,400mAh)
- **KNB-57L**
Li-ion Battery Pack
(2,000mAh)
- **KNB-40LCV**
Li-ion Battery Pack
(7.4V/1950mAh) I.S.
- **KBP-5**
Battery Case
- **KSC-25**
Rapid Charger
- **KSC-30**
Regular Charger
for KNB-56N



- **KSC-256K**
Six Unit
Gang Charger
- **KRA-22**
VHF Low Profile
Helical Antenna
- **KRA-23**
UHF Low Profile
Helical Antenna
- **KRA-26**
VHF Helical Antenna
- **KRA-27**
UHF Whip Antenna



- **KMC-45**
Speaker Microphone
- **KMC-21**
Speaker Microphone
- **KEP-2**
Earphone Kit for
KMC-45 (2.5mm plug)
- **KHS-22**
Head Set
- **KVC-3**
Regular Rate Vehicular
Charger Adapter
(for KSC-30)
- **KVC-4**
Rapid Rate Vehicular
Charger Adapter
(for KSC-25)



- **KHS-7A**
Lightweight Single
Muff Headset
- **KHS-8BL**
2-wire Palm Mic with
Earphone (Black)
- **KHS-9BL**
3-wire Lapel Mic
with Earphone (Black)
- **KLH-138**
Leather Case
- **KLH-139** - for DTMF Model
Leather Case
w/Swivel Belt Loop



Specifications

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

| Model | TK-2170 | TK-3170 |
|--|---|-----------------|
| GENERAL | | |
| Frequency Range | | |
| Type 1 | 136-174 MHz | 450-490 MHz |
| Type 3 | — | 400-430 MHz |
| Number of Channels | | |
| Zone | Max. 128 per Radio | |
| Conv. Ch | Max. 128 per Zone | |
| Channel Spacing | | |
| Wide/Narrow | 25, 30 kHz/12.5, 15 kHz | 25 kHz/12.5 kHz |
| Battery Voltage | 7.5V DC±20% | |
| Battery Life (5-5-90 duty cycle, during hi-power, battery saver off) | | |
| with KNB-55L (1480mAh) | Approx. 9 hours | |
| with KNB-56N (1400mAh) | Approx. 9 hours | |
| with KNB-57L (2000mAh) | Approx. 13 hours | |
| Operating Temperature Range* | -22°F ~ +140°F (-30°C ~ +60°C) | |
| Frequency Stability | ±2.5ppm (-22°F ~ +140°F) | |
| Antenna Impedance | 50 Ω | |
| Channel Frequency Spread | | |
| Type 1 | 38 MHz | 40 MHz |
| Type 3 | — | 30 MHz |
| Dimensions (W x H x D), Projections not included | | |
| Radio Only | 2.2 x 4.3 x 0.65 (56 x 109 x 16.6 mm) | |
| with KNB-55L | 2.2 x 4.3 x 1.21 (56 x 109 x 30.7 mm) | |
| with KNB-56N | 2.2 x 4.3 x 1.49 (56 x 109 x 37.9 mm) | |
| with KNB-57L | 2.2 x 4.3 x 1.25 (56 x 109 x 31.7 mm) | |
| Weight (net) | | |
| Radio Only | 7.2 oz. (205 g) (includes supplied accessories) | |
| with KNB-55L | 10.62oz. (302g) without antenna | |
| with KNB-56N | 14.15oz. (402g) without antenna | |
| with KNB-57L | 11.50oz. (327g) without antenna | |
| FCC ID | | |
| Type 1 | ALH34703110 | ALH34713110 |
| Type 3 | — | ALH34713130 |
| IC Certification | | |
| Type 1 | 282D-34703110 | 282D-34713110 |
| Type 3 | — | 282D-34713130 |

*+14°F ~ +140°F (-10°C ~ +60°C) when KNB-26N/35L in use

Applicable MIL-STD & IP

| Standard | MIL 810C Methods/Procedures | MIL 810D Methods/Procedures | MIL 810E Methods/Procedures | MIL 810F Methods/Procedures |
|--|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Low Pressure | 500.1/Procedure I | 500.2/Procedure I, II | 500.3/Procedure I, II | 500.4/Procedure I, II |
| High Temperature | 501.1/Procedure I, II | 501.2/Procedure I, II | 501.3/Procedure I, II | 501.4/Procedure I, II |
| Low Temperature | 502.1/Procedure I | 502.2/Procedure I, II | 502.3/Procedure I, II | 502.4/Procedure I, II |
| Temperature Shock | 503.1/Procedure I | 503.2/Procedure I | 503.3/Procedure I | 503.4/Procedure I, II |
| Solar Radiation | 505.1/Procedure I | 505.2/Procedure I | 505.3/Procedure I | 505.4/Procedure I |
| Rain | 506.1/Procedure I, II | 506.2/Procedure I, II | 506.3/Procedure I, II | 506.4/Procedure I, III |
| Humidity | 507.1/Procedure I, II | 507.2/Procedure II, III | 507.3/Procedure II, III | 507.4 |
| Salt Fog | 509.1/Procedure I | 509.2/Procedure I | 509.3/Procedure I | 509.4 |
| Dust | 510.1/Procedure I | 510.2/Procedure I | 510.3/Procedure I | 510.4/Procedure I, III |
| Vibration | 514.2/Procedure VIII, X | 514.3/Procedure I | 514.4/Procedure I | 514.5/Procedure I |
| Shock | 516.2/Procedure I, II, V | 516.3/Procedure I, IV | 516.4/Procedure I, IV | 516.5/Procedure I, IV |
| International Protection Standard | | | | |
| Dust & Water Protection | IP54/55 | | | |

*To meet MIL 810 and IP grade, the 2-pin connector cover has to be connected.

| Model | TK-2170 | TK-3170 |
|--|-------------------------------------|---------|
| RECEIVER (Measurements made per TIA/EIA-603) | | |
| Sensitivity (12dB SINAD) | | |
| Wide | | 0.25 μV |
| Narrow | | 0.28 μV |
| Selectivity | | |
| Wide | | 70 dB |
| Narrow | | 65 dB |
| Intermodulation Distortion | | |
| Wide | | 65 dB |
| Narrow | | 60 dB |
| Spurious Response | | 65 dB |
| Audio Output (4 Ω Impedance) | 500 mW with less than 5% distortion | |
| TRANSMITTER (Measurements made per TIA/EIA-603) | | |
| RF Output Power | | |
| High | 5 W | 4 W |
| Low | 1 W | 1 W |
| Spurious Response | | 70 dB |
| Type of Emission | | |
| Wide | 16K0F3E | |
| Narrow | 11K0F3E | |
| FM HUM & Noise | | |
| Wide | 45 dB | |
| Narrow | 43 dB | |
| Audio Distortion | Less than 5% | |

Specifications are subject to change without notice, due to advancements in technology.
FleetSync® is a registered trademark of JVC KENWOOD Corporation in the United States and/or other countries.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
All other trademarks are property of their respective owners.

Footnotes from front:

- ¹ Conventional Zones: 128 Channels /128 Zones max. per radio; 128 CH max. per Zone.
- ² Keypad models only.
- ³ Two-Tone Decode (3 sets x 2 pairs each); Single / Two-Tone Encode (10 tones), Operator Selectable Tone (40 QT.DQT code pairs).
- ⁴ DTMF Encode: PTT ID, Emergency ANI, Auto-Dial (16 numbers); Manual Encode (Keypad models), DTMF Decode: Code Squelch (3-10 digit), Selective Call (9-digit with status) Group Codes A, B, C, D & Wild Card characters) and radio Stun.
- ⁵ Special Alert Tone Patterns operate for 2-Tone, DTMF, FleetSync® selective call decode.
- ⁶ Call Key 1 & 2: operates for 2-Tone, DTMF and FleetSync® status encode.
- ⁷ KPG-101D required: Windows®98/NT/2000/Me/XP compatible; English/Spanish screen languages.
- ⁸ ID List capacity is 100 ID's; Short Text Messages are radio stored & LCD displayed; Status Message List capacity is 50.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.ca



www.kenwoodusa.com



ISO9001 Registered
Communications Equipment Division
Professional Systems Business Group
JVC KENWOOD Corporation
AJS#27812 Printed in USA