

KENWOOD

TK-2400/3400

Compact VHF/UHF FM 2-Watt Portable Radios

FleetSync®

GENERAL FEATURES

- 2 W (136-174 MHz) VHF
- 2 W (450-520 MHz) UHF
- 4 & 16 Channel Models
- Single Priority / Normal Scan
- Transmit / Busy / Call Alert Scan / Warn LED
- 4-Color LED (Blue/Red/Green/Orange)
- 2 PF Keys
- 1.0 W Speaker Audio
- Enhanced Kenwood Audio
- Companded Audio (per CH)
- Voice Annunciation
- VOX Ready
- Voice Inversion Scrambler Built-in
- 16 Scrambler Codes (per CH)
- Emergency Call Features
- Lone Worker Alert (per CH)
- QT / DQT
- Two-Tone Decode¹
- Single / Two-Tone Encode¹
- DTMF Encode / Decode²
- Special Alert Tone Pattern³
- Time Out Timer
- Busy Channel Lockout
- Low Battery Warning
- Battery Saver

- Windows® Programming & Tuning⁴
- Wireless Cloning
- Password Protection
- MIL-STD-810 C/D/E/F/G
- IP-54/55 Water & Dust Intrusion

FleetSync®

- PTT ID Digital ANI
- Selective Call & Group Call⁵
- Paging Call
- Emergency Status
- Send GPS Data (KMC-48GPS)

MDC-1200

- PTT ID Digital ANI
- Emergency Status
- Radio Check
- Radio Inhibit

ACCESSORIES INCLUDED

- KNB-45L Li-Ion Battery
- KSC-35SK 3-Hour Fast Charger
- KBH-10 Spring Action Belt Clip
- Removable Antenna



Options

■ KNB-29N Ni-MH Battery Pack (1,500mAh)	■ KRA-22 VHF Low Profile Helical Antenna	■ KEP-2 Earphone Kit for KMC-45 (2.5mm plug)	■ KHS-25 D-Ring Ear Hanger with PTT & Boom Mic
■ KNB-45L 2,000mAh/7.4V Li-Ion Battery Pack	■ KRA-23 UHF Low Profile Helical Antenna	■ KHS-7 Single Muff Headset	■ KHS-26 Earbud In-line PTT Headset
■ KSC-35SK Fast Charger For the KNB-45L (3-Hour)	■ KRA-26 VHF Helical Antenna	■ KHS-7A Single Muff Headset with In-line PTT	■ KHS-27 D-Ring In-line PTT Headset
■ KSC-43K Dual Chemistry Fast Charger For the KNB-29N/45L	■ KRA-27 UHF Whip Antenna	■ KHS-8BL 2-wire Palm Mic with Earphone (Black)	■ KHS-31 C-Ring PTT Ear Hanger Headset
■ KVC-22 DC Vehicular Charger Adapter	■ KMC-48GPS GPS Speaker Microphone	■ KHS-9BL 3-wire Lapel Mic with Earphone (Black)	■ KMB-28 Six Unit Charger Adapter (for six KSC-35SK chargers) (chargers not included)
■ KRA-41 VHF Stubby Antenna	■ KMC-45 Speaker Microphone	■ KHS-22 Behind-the-head Headset with PTT	■ KBH-10 Belt Clip
■ KRA-42 UHF Stubby Antenna	■ KMC-21 Compact Speaker Microphone	■ KHS-23 2-wire Palm Mic	■ KLH-187 Nylon Case

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-2400 VHF	TK-3400 UHF
GENERAL		
Frequency Range	136-174 MHz	450-520 MHz
Number of Channels		
K		4
K2		16
Channel Spacing		
Wide/Narrow	25 kHz / 12.5 kHz	
Operating Voltage	7.5V DC±20%	
Battery Life (5-5-90 duty cycle battery saver OFF)		
with KNB-45L (2000mAh)	More than 17 hours	
Operating Temperature Range*	-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability	±2.5ppm (-22°F ~ +140°F)	
Antenna Impedance	50 Ω	
Dimensions (W x H x D), Projections not included		
Radio Only	2.13 x 4.8 x 1.32 inch (54 x 122 x 33.7mm)	
with KNB-45L	2.13 x 4.8 x 1.32 inch (54 x 122 x 33.7mm)	
Weight (net)		
Radio Only	5.8oz (165g)	
with KNB-45L	9.9oz (281g)	
FCC ID	ALH434901	ALH435002

*-14°F ~ +140°F (-10°C ~ +60°C) When KNB-45L in use.

Model	TK-2400 VHF	TK-3400 UHF
RECEIVER (Measurements made per TIA/EIA-603)		
Sensitivity (12dB SINAD)		
Wide/Narrow	0.25µV/0.28µV	
Selectivity		
Wide/Narrow	70dB/60dB	
Intermodulation Distortion		
Wide/Narrow	70dB/60dB	
Spurious Response	70dB	
Audio Distortion	less than 10% distortion	
Audio Output	1 W / 12 Ω (Internal Speaker)	
	500mW / 8 Ω (External Speaker)	
TRANSMITTER (Measurements made per TIA/EIA-603)		
RF Power Output		
High/Low	2W/1W	
Spurious Response	70dB	
FM Hum & Noise		
Wide/Narrow	45/40dB	
Audio Distortion	Less than 5%	
Modulation		
Wide/Narrow	16K0F3E/11K0F3E	

Specifications are subject to change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVC/KENWOOD Corporation.

Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

Footnotes from front:

¹ Two-Tone Decode (3 sets x2 pairs each); Single / Two-Tone Encode (1 tone).

² DTMF Decode: PTT ID, Emergency ANI, Auto-Dial (8 numbers); DTMF Decode: Selective Call (10-digit ID Code, Group Codes; A, B, C, D, & Wild Card characters), and Radio Stun.

³ Special Alert Tone Pattern operates for 2-Tone, DTMF, FleetSync® selective call decode.

⁴ KPG-160D required: Windows®XP / Vista / 7 compatible.

⁵ ID List capacity: 8 ID's; 10 Group ID's; Status 1 & 2 (10-99).

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54/55*				

*To meet IP54/55, the 2-pin connector cover has to be connected on the radio or the locking bracket has to be attached to the KMC-45 external speaker microphone.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745



www.kenwoodusa.com



ISO9001 Registered
Professional Systems Business Group
JVC/KENWOOD Corporation

ADS#53312 Printed in USA